



RECOMMENDED PCB LAYOUT

备注:

1. 产品规格:

REV.	ECN.NO.	APPD.
A	XXXXXXXXXXXX	yanggufeng

- 1-1. 插入力: 35N MAX.
  - 1-2. 拔出力: 10N MIN. INITIAL 8-20N AFTER 3000 CYCLES
  - 1-3. 额定电流: 1.0A
  - 1-4. 额定电压: 30V
  - 1-5. 耐久性: 3000 CYCLES MIN.
  - 1-6. 耐电压: 100V AC MIN.
  - 1-7. 接触阻抗: 30mΩ MAX. INITIAL; 40mΩ MAX AFTER 3000 CYCLES
  - 1-8. 绝缘电阻: 100MΩ MIN
  - 1-9. 工作温度: -30° TO +80°
2. 材质:
- 2.1 胶芯: LCP UL94V-0
  - 2.2 端子: C2680R-H, 镍底, 镀金1μ"
  - 2.3 外壳: SUS 镀雾锡
3. 所用材质须符合RoHS要求
4. 重点尺寸标识"▲"符号

- U442-A916-XXXXX8
- 1: 铁壳镀镍
  - 2: 铜壳镀镍
  - 3: 半金3u"
  - 4: 镀全亮锡
  - 5: 半金5u"
  - 6: 不锈钢镀雾锡
  - G: 半金G/Pu"
  - 9: 镀全金1u"
- 1: 吸塑盒
  - 2: 吸塑管
  - 3: 载带
  - 6: 载带+贴麦拉
- 1: PA66
  - 2: PBT
  - 6: LCP
  - 1: 黑色
  - 2: 白色
  - 3: 米黄色

TOLERANCE UNLESS OTHERWISE SPECIFIED		HUA LIAN WEI TECHNOLOGY ELECTRONICS CO.,LTD.	
XXX ±0.10	XX ±0.20	X ±3	XX ±2
APPROVED		PART NAME: MICRO 5P 牛角6.6	
DRAWN: yanggufeng		PART No: U442-A916-G61038	
DATE: 2021.12.01		PROJECTION:	
		UNIT: mm	SCALE: 1:1
		SHEET: 1 OF 1	REV: A

HLW 深圳市华联威电子科技有限公司