



特性: Specifications:

电器: Electrical:

接触阻抗: Contact Resistance

50 milliohms MAX

耐电压: Dielectric Withstanding Voltage:

100 V AC AT Sea Level

绝缘阻抗: Insulation Resistance:

100 MEGA ohms MIN

材料: Material:

塑胶: Housing: High Temperature Thermoplastics,  
UL 94V-0 耐高温塑胶

端子: Contact: Copper Alloy 铜合金

铁壳: Shell: Copper Alloy 铜合金

电镀: Finish:

端子: Contact: Plated Gold in Mating Area;

Tin On Solder Tails

接触点镀金. 脚镀锡

铁壳: Shell:

Nickel/ Plating 镀镍

TOLERANCE UNLESS OTHERWISE SPECIFIED		FLW 深圳市华联威电子科技有限公司			
.XXX ±0.10	.X' ±3'	HUA LIAN WEI TECHNOLOGY ELECTRONICS CO.;LTD.			
.XX ±0.20	.XX' ±2'				
.X ±0.30					
APPROVED		PART NAME:	MINI 8P/F 四脚全贴		
CHECKED		PART No:	U142-1755-G61078	C	
DRAWN	weihong	PROJECTION:	UNIT:	SCALE	SHEET
DATE	2021.7.23		mm	1:1	10F1
					REV. A